

(19) World Intellectual Property
Organization
International Bureau



549800

(43) International Publication Date
30 September 2004 (30.09.2004)


PCT

(10) International Publication Number
WO 2004/084375 A2

- (51) International Patent Classification⁷: **H02K** (74) Agent: LEDBETTER, James, Edward; Stevens, Davis, Miller & Mosher, LLP, 1615 L. Street, NW, Suite 850, Washington, DC 20036 (US).
- (21) International Application Number: PCT/US2004/008114
- (22) International Filing Date: 17 March 2004 (17.03.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/454,630 17 March 2003 (17.03.2003) US
- (71) Applicant (for all designated States except US): VIRGINIA TECH INTELLECTUAL PROPERTIES, INC.; 1872 Pratt Drive, Suite 1625, Blacksburg, VA 24060 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): RAMU, Krishnan [US/US]; 419 Ridgeview Drive, Blacksburg, VA 24060 (US). LOBO, Savio, Nimal [IN/US]; 2512 Manchester Street, Blacksburg, VA 24060 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: APPARATUS AND METHOD THAT PREVENT FLUX REVERSAL IN THE STATOR BACK MATERIAL OF A TWO-PHASE SRM (TPSRM)



(57) Abstract: A TPSRM may include a stator, having a plurality of poles and a ferromagnetic or iron back material, and a rotor having a plurality of poles and a ferromagnetic or iron back material. A current flowing through coils wound around a first set of the plurality of stator poles induces a flux flow through the first set of stator poles and portions of the stator back material during a first excitation phase. A current flowing through coils wound around a second set of the plurality of stator poles induces a flux flow through the second set of stator poles and portions of the stator back material during a second excitation phase. The numbers of stator and rotor poles for this TPSRM are selected such that substantially no flux reversal occurs in any part of the stator back material as a result of transitioning between the first and second excitation phases.

WO 2004/084375 A2



Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.